Formulating a Greener World®

SoluJET® 27010

Solvent ink for non-porous media















TECHNICAL DATA SHEET

SoluJET® 2701O orange solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications.

SoluJET® 2701O ink provides good adhesion and rub resistance, fast drying time, and excellent sharpness on semi-porous and non-porous substrates such as lacquered aluminum foils and packaging films.⁽¹⁾

Technical Specifications

	SoluJET® 27010 Print Cartridge
Ink type	Orange dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300×300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.0 V
Fire pulse width	1.8 μs
Pulse warming	OFF
Decap time(1)	5 min
Drying time ⁽¹⁾	$5 - 7 \text{ s at } 300 \times 300 \text{ dpi}$
Throw distance ⁽²⁾	Up to 5 mm, recommended 3 mm
Average delivered ink	36 mL (vertical)
Average drop volume	34 pL `
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	5 °C to 30 °C
Best before ⁽³⁾	4 months from filling date

Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	Product description
2701O42A	SoluJET® 27010 Print Cartridge

⁽¹⁾ Ink performance may vary depending on substrate, printer, and environmental conditions.

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 294 3846 997 - Fax: +84 294 3846 998

Email: inks@mylangroup.com Website: www.mylangroup.com

⁽²⁾ Recommended. May vary by application.

⁽³⁾ Must be shipped and stored under recommended conditions.