Formulating a Greener World®

SoluJET®2704B

Solvent ink for non-porous media











TECHNICAL DATA SHEET

SoluJET® 2704B blue solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications.

SoluJET® 2704B ink provides good adhesion and rub resistance, excellent sharpness and barcode readability on various semi-porous and non-porous substrates such as nitrocellulose or acrylic coated foils and flexible packaging films.⁽¹⁾

Technical Specifications

Ink name	SoluJET® 2704B
Ink type	Blue dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 x 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.0 V
Fire pulse width	1.8 µs
Pulse warming	Off
Decap time(1)	1 min
Drying time(1)	5 - 7 sec at 300 x 300 dpi
Throw distance ⁽²⁾	Up to 5 mm, recommended 3 mm
Average delivered ink	40 mL (vertical)
Average drop volume	35 pL
Operating conditions	15°C to 35°C, 35% to 80% RH
Shipping / storage temperature	5°C to 30°C
Shelf life ⁽³⁾	4 months from filling date

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (>98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Cartridge Shipping & Storage

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- · Avoid direct light.
- Refer to Safety Data Sheet for more information.

Ordering Information

Product number	Product description	0000
2704B42A	SoluJET® 2704B Print Cartridge	

⁽¹⁾ Ink performance may vary depending on substrate, printer, and environmental conditions

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel: +84 2943 846 997 - Fax: +84 2943 846 998

Email: inks@mylangroup.com Website: www.mylangroup.com

⁽²⁾ Recommended. May vary by application.

⁽³⁾ Must be shipped and stored under recommended conditions