

Formulating a Greener World®

HydraJET® 2018K

Aqueous ink for porous media



TECHNICAL DATA SHEET

HydraJET® 2018K black aqueous TIJ 2.5 ink is designed for track and trace coding and marking and high-productivity industrial printing applications such as wood, packaging, label, mailing and ticket printing.

HydraJET® 2018K ink provides excellent fade resistance and water resistance, long decap time, excellent darkness, sharpness, and barcode readability on various porous and semi-porous substrates such as wood, plain paper, cardboard, duplex board, and semi-porous coated paper.⁽¹⁾

Technical Specifications

Ink name	HydraJET® 2018K
Ink type	Black dye-pigment aqueous ink
Print cartridge type	HP 45ai
Resolution	Up to 600 dpi, recommended 300 × 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	11.0 V
Fire pulse width	1.8 µs
Pulse warming	OFF
Decap time ⁽¹⁾	Up to 2 h
Drying time ⁽¹⁾	2 s at 300 × 300 dpi
Throw distance ⁽²⁾	Up to 3 mm, recommended 1 mm
Average delivered ink	42 mL (vertical)
Average drop volume	27 pL
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	10 °C to 35 °C
Shelf life ⁽³⁾	12 months from filling date

Cartridge Shipping & Storage

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with deionized water to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	Product description
2018K42A	HydraJET® 2018K Print Cartridge

(1) Ink performance may vary depending on substrate, printer, and environmental conditions.

(2) Recommended. May vary by application.

(3) Must be shipped and stored under recommended conditions.

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 2943 846 997 - Fax: +84 2943 846 998

Email: inks@mylangroup.com

Website: www.mylangroup.com