Formulating a Greener World®







# **TECHNICAL DATA SHEET**

HydraJET<sup>®</sup> 2018K black aqueous TIJ 2.5 ink is designed for track and trace coding and marking and high-productivity industrial printing applications such as wood, packaging, label, mailing and ticket printing.

HydraJET® 2018K ink provides excellent fade resistance and water resistance, long decap time, excellent darkness, sharpness, and barcode readability on various porous and semi-porous substrates such as wood, plain paper, cardboard, duplex board, and semi-porous coated paper.

### **Technical Specifications**

|                           | HydraJET <sup>®</sup> 2018K Bulk Printhead | HydraJET® 2018K Bulk Ink Reservoir |
|---------------------------|--|------------------------------------|
| Ink type                  | Black dye-pigment aqueous ink              | Black dye-pigment aqueous ink      |
| Print cartridge type      | HP 45ci                                    |                                    |
| Resolution                | Up to 600 dpi, recommended                 |                                    |
|                           | 300 × 300 dpi                              |                                    |
| Nozzle count              | 300  |                                    |
| Print swath               | 12.7 mm                                    |                                    |
| Firing voltage            | 11.0 V                                     |                                    |
| Fire pulse width          | 1.8 μs                                     |                                    |
| Pulse warming             | OFF  |                                    |
| Decap time                | Up to 2 h                                  |                                    |
| Drying time               | 2 s at 300 × 300 dpi                       |                                    |
| Throw distance            | Up to 3 mm                                 |                                    |
| Average bulk delivered in | 420 mL (vertical)                          |                                    |
| Average drop volume       | 27 pL                                      |                                    |
| Operating conditions      | 15 °C to 35 °C, 35% to 80% RH              | 15 ℃ to 35 ℃, 35% to 80% RH        |
| Shipping / storage        | 10 ℃ to 35 ℃                               | 10 °C to 35 °C                     |
| temperature               |  |                                    |
| Best before               | 12 months from filling date                | 12 months from filling date        |

## **Cartridge Shipping & Storage**

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

### **Cartridge Maintenance & Handling**

- Use a lint-free cloth moistened with deionized water to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth

to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
Do not shake the cartridge.

### **Ordering Information**

| Product number | Product description            |  |
|----------------|--------------------------------|--|
| 2018K44S       | ydraJET® 2018K Bulk Ink System |  |

#### MYLAN GROUP Longduc Industrial Park, Travinh City, Travinh Province, Vietnam Tel.: +84 294 3846 997 - Fax: +84 294 3846 998 Email: info@mylangroup.com Website: www.mylangroup.com