

Formulating a Greener World®

HydraJET® 2020K

Aqueous ink for porous media

BULK INK SYSTEM



Mylan
Formulating a Greener World®

2020K44B
High efficiency, cost saving bulk ink

400 mL

WARNING
Causes mild skin irritation.
Causes eye irritation.
Store in a well-ventilated place. Keep cool.

MYLAN GROUP
Long Duc Industrial Park, Travinh City,
Binh Duong Province, Vietnam
Tel: +84 2943 846 997 - Fax: +84 2943 846 998
Email: info@mylangroup.com Website: www.mylangroup.com

HydraJET 2020K
Aqueous ink for porous media

Mylan

HydraJET 2020K
Aqueous ink for porous media

TECHNICAL DATA SHEET

HydraJET® 2020K black aqueous TIJ 2.5 ink is designed for track and trace coding and marking at high-productivity industrial printing applications such as packaging, label, mailing and ticket printing.

HydraJET® 2020K ink provides enhanced fade resistance and water resistance, long decap time, excellent darkness, sharpness, and barcode readability on various porous and semi-porous substrates such as plain paper, cardboard, duplex board, and semi-porous coated paper.

Technical Specifications

	HydraJET® 2020K Bulk Printhead	HydraJET® 2020K Bulk Ink Reservoir
Ink type	Black dye aqueous ink	Black dye aqueous ink
Print cartridge type	HP 45ci	
Resolution	Up to 600 dpi, recommended 300 x 300 dpi	
Nozzle count	300	
Print swath	12.7 mm	
Firing voltage	11.0 V	
Fire pulse width	1.8 µs	
Pulse warming	OFF	
Decap time	Up to 30 min	
Drying time	1 - 3 s at 300 x 300 dpi	
Throw distance	Up to 3 mm	
Average bulk delivered ink	420 mL (vertical)	
Average drop volume	27 pL	
Operating conditions	15 °C to 35 °C, 35% to 80% RH	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	10 °C to 35 °C	10 °C to 35 °C
Best before	12 months from filling date	12 months from filling date

Cartridge Shipping & Storage

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with deionized water to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	Product description
2020K44S	HydraJET® 2020K Bulk Ink System

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 294 3846 997 - Fax: +84 294 3846 998

Email: info@mylangroup.com

Website: www.mylangroup.com