Formulating a Greener World®

HydraJET® 2022R

Aqueous ink for porous media

Mylan® GROUP
Formulating a Greener World®

ISO 14001 SYSTEM CERTIFICATION SGS
UKAS ENVIRONMENTAL MANAGEMENT 005
GUARDIAN INDEPENDENT CERTIFICATION GIC ISO 9001 : 2015
UKAS QUALITY MANAGEMENT 045

TECHNICAL DATA SHEET

HydraJET® 2022R red aqueous TIJ 2.5 ink is designed for industrial printing applications such as packaging, mailing and ticket printing.
HydraJET® 2022R ink provides long decap time, high optical density, good fade resistance, and excellent sharpness on various porous and semi-porous substrates such as plain paper, cardboard, duplex board, and semi-porous coated papers.

Technical Specifications

	HydraJET® 2022R Print Cartridge
Ink type	Red dye aqueous ink
Print cartridge type	HP 45ai
Resolution	Up to 600 dpi, recommended 300 × 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	11.0 V
Fire pulse width	1.8 µs
Pulse warming	OFF
Decap time	Up to 1 h
Drying time	1 – 3 s at 300 × 300 dpi
Throw distance	Up to 3 mm
Average delivered ink	40 mL (vertical)
Average drop volume	27 pL
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	10 °C to 35 °C
Best before	12 months from filling date

Cartridge Shipping & Storage

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with deionized water to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	**Product description**
2022R42A	HydraJET® 2022R Print Cartridge

MYLAN GROUP
Long Duc Industrial Park, Long Duc Ward, Vinh Long Province, Vietnam
Tel.: +84 294 3846 997 - Fax: +84 294 3846 998
Email: info@mylangroup.com
Website: www.mylangroup.com