

HydraJET[®] 8052K

Aqueous Piezoelectric Inkjet Ink

TECHNICAL DATA SHEET

HydraJET[®] 8052K black aqueous PIJ ink is designed for inkjet printers that equipped with piezoelectric printheads. The ink provides high-productivity industrial performance across a wide range of label, ticket, and packaging printing applications.

HydraJET[®] 8052K ink provides excellent fade resistance, smear resistance and water resistance, excellent optical density, crisp text and barcodes on various porous substrates such as wood, cardboard and plain paper.⁽¹⁾

Technical Specifications

Ink name	HydraJET[®] 8052K
Ink type	Black pigment aqueous ink
Decap time⁽¹⁾	Up to 1 h
Drying time⁽¹⁾	2 s at 360 x 360 dpi – 1 drop
Operating conditions	10 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	5 °C to 30 °C
Shelf life⁽²⁾	12 months from filling date

Recommended Jetting Parameters

Printhead	Konica Minolta KM1024	Konica Minolta KM512	Ricoh Gen 4
Printhead temperature	35 °C – 42 °C	35 °C – 42 °C	35 °C – 42 °C
Waveform	5.6/11.2/11.2 μs	5.6/11.2/11.2 μs	2/2.5/2/9 μs

Shipping & Storage

- The ink should be stored in cold and dry place, avoid direct light.
- Please refer to Safety Data Sheets for more information.

Handling

- Slightly shaking the ink before use is recommended.
- Cleaning and flushing printhead by HydraJET[®] 8050F flushing solution.

Ordering Information

Product number	Product description
8052K01P	HydraJET [®] 8052K

(1) Ink performance may vary depending on substrate, printer, and environmental conditions.

(2) Must be shipped and stored under recommended conditions.

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam
Tel.: +84 294 3846 997 - Fax: +84 294 3846 998
Email: inks@mylangroup.com
Website: www.mylangroup.com