

Formulating a Greener World®

SoluJET® 2701W

Solvent ink for non-porous media



TECHNICAL DATA SHEET

SoluJET® 2701W white pigmented solvent TIJ 2.5 ink is specially designed for coding and marking on dark and clear semi-porous non-porous substrates.

SoluJET® 2701W ink provides excellent fade resistance and heat resistance, fast drying time on semi-porous and non-porous substrates such as coated paper, plastics, metals and foils.⁽¹⁾

Technical Specifications

	SoluJET® 2701W Print Cartridge
Ink type	White pigment solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 × 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.0 V
Fire pulse width	2.2 µs
Pulse warming	OFF
Decap time⁽¹⁾	5 min
Drying time⁽¹⁾	3 - 4 s at 300 × 300 dpi
Throw distance⁽²⁾	Up to 5 mm, recommended 3 mm
Average delivered ink	35 mL (vertical)
Average drop volume	33 pL
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	5 °C to 30 °C
Best before⁽³⁾	2 months from filling date

Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. NOZZLES UP position is recommended.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Lightly shake the cartridge capped with clip 10 to 20 times before use.
- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.

Ordering Information

Product number	Product description
2701W42A	SoluJET® 2701W Print Cartridge

(1) Ink performance may vary depending on substrate, printer, and environmental conditions.

(2) Recommended. May vary by application.

(3) Must be shipped and stored under recommended conditions.

MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 294 3846 997 - Fax: +84 294 3846 998

Email: inks@mylangroup.com

Website: www.mylangroup.com