# Formulating a Greener World®

# SoluJET® 2706K

Solvent ink for non-porous media















#### TECHNICAL DATA SHEET

SoluJET® 2706K black solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications.

SoluJET® 2706K ink provides fast drying time, excellent adhesion and rub resistance, high optical density, and excellent sharpness and barcode readability on various semi-porous and non-porous substrates such as metal, PET, PVC, PA, BOPP film and foils.

#### **Technical Specifications**

	SoluJET® 2706K Print Cartridge
Ink type	Black dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended $300 \times 300$ dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	8.8 V
Fire pulse width	1.6 μs
Pulse warming	OFF
Decap time	30 min
Drying time	1 - 3 s at $300 \times 300$ dpi
Throw distance	Up to 5 mm
Average delivered ink	36 mL (vertical) and 34 mL (horizontal)
Average drop volume	38 pL ( )
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	5 °C to 30 °C
Best before	9 months from filling date

#### **Cartridge Shipping & Storage**

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Horizontal position is recommend.
- Refer to Safety Data Sheet for more information.

## Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

## **Ordering Information**

Product number	Product description
2706K42A	SoluJET® 2706K Print Cartridge

#### **MYLAN GROUP**

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 294 3846 997 - Fax: +84 294 3846 998

Email: info@mylangroup.com Website: www.mylangroup.com