Formulating a Greener World®

SoluJET® 2707R

Solvent ink for non-porous media

Mylan GROUP
Formulating a Greener World®

Vietnam Value

ISO 14001 SYSTEM CERTIFICATION SGS

UKAS ENVIRONMENTAL MANAGEMENT 005

GUARDIAN INDEPENDENT CERTIFICATION GIC ISO 9001 : 2015

UKAS QUALITY MANAGEMENT 045

TECHNICAL DATA SHEET

SoluJET® 2707R red solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications.
SoluJET® 2707R ink provides long decap time, good adhesion and rub resistance, excellent sharpness and high optical density PET, PVC, PA, BOPP and foils.

Technical Specifications

	SoluJET® 2707R Print Cartridge
Ink type	Red dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 × 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	8.6 V
Fire pulse width	2.0 µs
Pulse warming	OFF
Decap time	Up to 1 h
Drying time	1 - 3 s at 300 × 300 dpi
Throw distance	Up to 5 mm
Average delivered ink	36 mL (vertical)
Average drop volume	34 pL
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	5 °C to 30 °C
Best before	6 months from filling date

Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	**Product description**
2707R42A	SoluJET® 2707R Print Cartridge

MYLAN GROUP
Long Duc Industrial Park, Long Duc Ward, Vinh Long Province, Vietnam
Tel.: +84 294 3846 997 - Fax: +84 294 3846 998
Email: info@mylangroup.com
Website: www.mylangroup.com