# Formulating a Greener World®









## **TECHNICAL DATA SHEET**

SoluJET® 2707W white pigmented solvent TIJ 2.5 ink is specially designed for coding and marking on dark and clear semi-porous non-porous substrates.

SoluJET® 2707W ink provides good print quality, high sharpness, white printing on dark packaging surfaces, high optical density in a single pass, fast dry time on both coated and uncoated substrates such glossy boxes, plastics, metals and foils.

#### **Technical Specifications**

	SoluJET <sup>®</sup> 2707W Print Cartridge
Ink type	White pigment solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 $ imes$ 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.2 V
Fire pulse width	2.4 μs
Pulse warming	OFF
Decap time	2 min
Drying time	3 - 5 s at 300 × 300 dpi
Throw distance	Up to 5 mm
Average delivered ink	35 mL (vertical)
Average drop volume	35 pL
Operating conditions	15 °C to 35 °C, 35% to 80% RH
Shipping / storage temperature	10 °C to 30 °C
Best before	4 months from filling date

### **Cartridge Shipping & Storage**

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. NOZZLES UP position is recommended.
- Refer to Safety Data Sheet for more information.

### **Cartridge Maintenance & Handling**

- Lightly shake the cartridge capped with clip 10 to 20 times before use.
- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.

• Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.

### **Ordering Information**

Product number	Product description
2707W42A	SoluJET <sup>®</sup> 2707W Print Cartridge