

**Formulating a Greener World®**

# SoluJET®2720R

Solvent ink for penetrable media



# TECHNICAL DATA SHEET

SoluJET® 2720R black solvent TIJ 2.5 ink is formulated to penetrate into rigid polyvinyl chloride, polycarbonate, polyurethane, nitrocellulose/ acrylic coated, and other penetrable substrates resulting a permanent printed output.

SoluJET® 2720R ink provides fast and completed penetrating, excellent rub resistance and chemical resistance, good decap time and optical density.

## Technical Specifications

<b>Ink name</b>	<b>SoluJET® 2720R</b>
<b>Ink type</b>	Red dye solvent ink
<b>Print cartridge type</b>	HP 45si
<b>Resolution</b>	Up to 600 dpi, recommended 300 x 300 dpi
<b>Nozzle count</b>	300
<b>Print swath</b>	12.7 mm
<b>Firing voltage</b>	9.0 V
<b>Fire pulse width</b>	2.2 µs
<b>Pulse warming</b>	Off
<b>Decap time<sup>(1)</sup></b>	10 min
<b>Drying time<sup>(1)</sup></b>	3 – 5 sec on rigid PVC pipe at 300 x 300 dpi
<b>Throw distance<sup>(2)</sup></b>	Up to 5 mm, recommended 3 mm
<b>Average delivered ink</b>	40 mL (vertical)
<b>Average drop volume</b>	36 pL
<b>Operating conditions</b>	15°C to 35°C, 35% to 80% RH
<b>Shipping / storage temperature</b>	5°C to 30°C
<b>Shelf life<sup>(3)</sup></b>	4 months from filling date

## Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (>98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

## Cartridge Shipping & Storage

- Store the cartridge with a clip placed over the printhead. Nozzles up or horizontal.
- Avoid direct light.
- Refer to Safety Data Sheet for more information.

## Ordering Information

<b>Product number</b>	<b>Product description</b>
2720R42A	SoluJET® 2720R Print Cartridge

(1) Ink performance may vary depending on substrate, printer, and environmental conditions.

(2) Recommended. May vary by application.

(3) Must be shipped and stored under recommended conditions.

### MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel: +84 2943 846 997 - Fax: +84 2943 846 998

Email: [inks@mylangroup.com](mailto:inks@mylangroup.com)

Website: [www.mylangroup.com](http://www.mylangroup.com)