

GHS SAFETY DATA SHEET

1 - Identification

Product identifier SoluJET® 2750W

Other means of identification Not available

Synonym(s) 2750 White solvent ink

Recommended use Inkjet Printing

Recommended restrictions None Known

Issue date 12-October-2016

Company identification MYLAN GROUP

Long Duc Industrial Park

Tra Vinh City, Tra Vinh Province, Vietnam

Tel. 84-74-3846-997 Fax 84-74-3846-998

2 - Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Not classified.

OSHA hazard(s) Not classified.

Label elements



Signal word Danger

Hazard statement H225- Highly flammable liquid and vapor.

H315- Causes skin irritation.

H317- May cause an allergic skin reaction. H319- Causes serious eye irritation.

Precautionary statement

Prevention P210 - Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P280 - Wear protective gloves/protective clothing/eye protection/face

protection.

P273 - Avoid release to the environment.

P370+P378- In case of fire: for small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam to extinguish. For large fires, use water spray, fog, or alcohol-resistant foam to extinguish. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT

use straight streams of water.

Response P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower.

Material name: SoluJET® 2750W

Storage P403 + P235 - Store in a well-ventilated place. Keep cool. **Disposal** P501- Dispose of contents/container in accordance with local/regional/national/international regulations. Hazard(s) not otherwise Not classified. classified (HNOC) **Environmental hazards** Hazardous to the aquatic environment, long-term hazard Category 3 3 - Composition/information on ingredients **Mixtures Hazardous components CAS Number** % **Chemical name** Ethyl alcohol 64-17-5 <40 1,6-Hexanediol diacrylate 13048-33-4 >20 Acrylic resin **Proprietary** >5 Bis(2,4,6-trimethylbenzoyl)-162881-26-7 <7 phenylphosphineoxide Colorants **Proprietary** <6 Additives Proprietary <2 4. First-aid measures Inhalation Move person to fresh air immediately. If symptoms persist, get immediate medical attention. Skin contact In case of contact, immediately remove contaminated clothing and flush skin with copious amounts of water. Wash clothing separately before reuse. Get medical attention, if needed. Eye contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately. Rinse mouth out with water. If the material is swallowed, get immediate Ingestion medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately. Most important symptoms/ See section 8. effects, acute and delayed 5. Fire-fighting measures **FLASH POINT:** 20°C (closed-cup) Suitable extinguishing media Suitable extinguishing media: sand, carbon dioxide (CO2) or dry chemical. Unsuitable extinguishing Not available. media Specific hazards arising from Not applicable. the chemical

Material name: SoluJET® 2750W

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing including self-contained breathing apparatus. Avoid run off into storm sewers and ditches which

lead to waterways.

Fire-fighting

equipment/instructions

Move containers from fire area if you can do it without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Avoid contact with skin. Avoid inhalation of vapors or mists.

Do not touch or walk through spilled material. Ensure adequate ventilation.

Remove all sources of ignition.

Use personal protective equipment to minimize exposure to skin and eye. In the case of vapor formation use a respirator with an approved filter.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Not available.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists

of this product.

Use with adequate ventilation.

Wear personal protective equipment.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place.

Keep away from heat, sparks and flame.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for

Air Contaminants

(29 CFR1910.1000)

Components	Type	Value

Ethyl alcohol (CAS 64-17-5) PEL 1900 mg/m3

1000 ppm

US. ACGIH Threshold Limit

Values

Components Type Value

Ethyl alcohol (CAS 64-17-5) STEL 1000 ppm

US. NIOSH: Pocket Guide to

Chemical Hazards

Components Type Value

Ethyl alcohol (CAS 64-17-5) TWA 1900 mg/m3

1000 ppm

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Not available.

Individual protection

measures, such as personal protective equipment

Material name: SoluJET® 2750W

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Eye wash fountain and emergency showers are recommended.

Skin protection

Hand protection Not available.

Other Wear appropriate chemical resistant clothing.

Wear appropriate chemical resistant gloves.

Respiratory protection Provide adequate ventilation. In case of insufficient ventilation wear

suitable respiratory equipment.

Thermal hazards Not available.

General hygiene Do not get this material in contact with skin. Avoid contact with skin, eyes

considerations and clothing.

When using, do not eat, drink or smoke. Wash hands before breaks and

immediately after handling the product.
Launder contaminated clothing before reuse.

9. Physical and chemical properties

Appearance White liquid

Odor Not available
Odor threshold Not available

pH Not available

Melting point/freezing point; Not available

Initial boiling point and boiling >70°C

range

Flash point 20°C (closed-cup)

Evaporation rate Not available

Flammability (solid, gas) Not applicable

Upper/lower flammability or

explosive limits

Flammability limit - lower

(%)

Not available

Flammability limit -

upper (%)

Not available

Explosive limit - lower

(%)

Not available

Explosive limit - upper

(%)

Not available

Vapor pressure Not available

Vapor density Not available

Relative density Not available

Solubility(ies) Soluble in Ethyl alcohol

Material name: SoluJET® 2750W

Partition coefficient: n-

Not available

octanol/water

Auto-ignition temperature

Not available

Decomposition temperature

Not available

Viscosity

Not available

10. Stability and reactivity

Reactivity

Not available.

Chemical stability

Stable at normal conditions.

Possibility of hazardous

reactions

None known.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Not available.

Hazardous decomposition

products

Not available.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological

effects

Acute toxicity value

Components Species Test results

Ethyl alcohol I (CAS 64-17-5)

Acute

Inhalation

LC50 Mouse 39 mg/l, 4 Hours

Rat 20000 mg/l, 10 Hours

Oral

LD50 Dog 5.5 g/kg

Guinea pig 5.6 g/kg

Mouse Mouse 3450 mg/kg
Rat Rat 7060 mg/kg

6.2 g/kg

1,6-Hexanediol diacrylate (CAS 13048-33-4)

Inhalation

LC50 Rat-Male and female 0,41 mg/l, 7 Hours

Oral

LD50 Rat 5000 mg/kg

Dermal

LD50 Rabbit 3650 mg/kg

Material name: SoluJET® 2750W

Skin corrosion/irritation

Skin Rabbit Irritating to skin. - 4 h

Skin corrosion/irritation Skin Contact: May cause skin irritation.

Skin Absorption: May be harmful if absorbed through the skin.

Serious eye damage/eye

Eye Contact: May cause eye irritation. irritation

Inhalation: May be harmful if inhaled. Material may be irritating to mucous

membranes and upper respiratory tract. Ingestion: May be harmful if swallowed.

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Specific target organ toxicity

- single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity

- repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12. Ecological information

Aquatic toxicity

Ecotoxicity

Components	Species	Test Results
------------	---------	--------------

Ethyl alcohol (CAS 64-17-5)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 7.7 - 11.2 mg/l, 48 hours

Fish LC₅₀ Fathead minnow (Pimephales > 100 mg/l, 96 hours

promelas)

1,6-Hexanediol diacrylate

(CAS 13048-33-4)

Fish LC50 Fish 10mg/l ,96hr

Crustacea LC50 Daphnia magna 2,6mg/l, 48hr

Algæ EC50 Green algae 1,5mg/l, 72hr

Bacteria Bacteria EC50 270 mg/l, 30min

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol /

water (log Kow)

Ethyl alcohol (CAS 64-17-5) -0.31

Mobility in soil Not available.

Material name: SoluJET® 2750W

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Do not dispose of together with general office waste.

Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and

Provincial Environmental Regulations.

Ensure collection and disposal with an appropriately licensed waste

contractor.

Local disposal regulations Not available.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

14. Transport information

DOT

UN number UN1210

UN proper shipping name Printing ink, flammable (Ethyl alcohol)

Transport hazard class(es) 3

Subsidiary class(es) Not available.

Packing group

Special precautions for

user

Passenger aircraft
Quantity limitation: 5 L

Cargo aircraft

Quantity limitation: 60 L Special provisions 24, IB2, T4, TP1

Labels required Not available.

IATA

UN number UN1210

UN proper shipping name Printing ink, flammable (Ethyl alcohol)

Transport hazard class(es) 3

Subsidiary class(es) -

Packaging group

Environmental hazards No

Labels required Not available.

ERG Code Not available.

Material name: SoluJET® 2750W

Special precautions for

Passenger and Cargo

user

Aircraft
Quantity limitation: 5 L

Cargo Aircraft Only
Quantity limitation: 60 L
Limited Quantities Passenger Aircraft
Quantity limitation: 1 L

IMDG

UN number UN1210

UN proper shipping name Printing ink, flammable (Ethyl alcohol)

Transport hazard class(es) 3

Subsidary class(es) -

Packaging group

Environmental hazards

Marine pollutant No

Labels required Not available.

EmS Not available.

Special precautions for

user

Not available.

Section 15 - Regulatory Information

US EPA TSCA Inventory: All chemical substances in this product comply

with all rules or orders under TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707,

Subpt. D)

Not regulated.

Not on regulatory list.

US. OSHA Specifically

Regulated Substances (29 CFR

1910.1001-1050)

CERCLA Hazardous Not on regulatory list.

Substance List (40 CFR 302.4)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance-No

SARA 311/312

Hazardous chemical-No

Material name: SoluJET® 2750W

US state regulations

US. Massachusetts RTK -

Substance List

Ethyl alcohol (CAS 64-17-5)

US. New Jersey Worker and

Community Right-to-Know Act

Not on regulatory list.

US. Pennsylvania RTK - Hazardous Substances

Ethyl alcohol (CAS 64-17-5)

US. Rhode Island RTK

Ethyl alcohol (CAS 64-17-5)

US - California Proposition 65 -

Carcinogens & Reproductive

Toxicity (CRT): Listed

substance

Not on regulatory list.

Section 16 - Other Information

Issue date 12-October-2016

Revision date -

Version # 01

Disclaimer This Safety Data Sheet document is provided without charge to customers

of Mylan Group. Data is the most current known to Mylan Group at the time of preparation of this document and is believed to be accurate. My Company makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory

requirements in other countries.

Material name: SoluJET® 2750W